

# Ultrasonic Leak Detector

## MODEL GS-5800

- Ultrasonic leak detector ideal for locating leaks generated by pressure, vacuum, water, gas or air
- Complete with Ultrasonic Leakage Detector, Ultrasonic Transmitter, rubber bottle plug with plastic tubing, 1/2" PVC pipe assembly for attaching to top of detector, 9V battery, and soft carrying case
- Leakage level is displayed by an LED bargraph and audible signal
- Ultrasonic Transmitter sends a 40 kHz signal which, when detected by the meter, indicates the location and magnitude of a leak
- Crystal time and oscillator circuit



Detector Frequency Response:  
20 to 100 kHz

Transmitter Frequency: 40 kHz

Dimensions: Detector: 10 x 2.8 x 1.1"  
(225 x 70 x 28mm)

Weight: 2 lb 14 oz

**GS-5800**  
**GS-400**

**Ultrasonic Leak Detector**  
**Ultrasonic Transmitter**

# Microwave Leakage Detector

## MODEL ST-2G

- Detects very low levels of microwave leakage
- Audible (beep) and visual (flashing red light) alarm signals
- Highly visible 5-digit LCD with backlight
- Built-in memory recalls maximum and minimum values, as well as last value stored
- Includes soft carrying case and batteries



Measuring Range: 0 to 9.99 mW/cm<sup>2</sup>

Alarm Level: 5.0 mW/cm<sup>2</sup>

Power Supply: Single 9V battery

Dimensions: 160 x 60 x 42mm

Weight: 151g

**ST-2G**

**Microwave Leakage Detector**